

Large Animal Operating Tables



Non-Heated Flat-Top Operating Table with Single Tilting and Hydraulic-Lift Base



Heated V-Top Operating Table with Single Tilting and Pedestal Base

These sturdy operating tables are for use with animals up to 136.2 kg (300 lb) and are available with any combination of the below features:

- V-top or flat-top
- Pedestal or hydraulic-lift base
- Single or dual tilting mechanism
- Heated or non-heated top

V-Top

The v-top table is 147.5 x 48 cm (58 x 19 in). Each panel adjusts independently from horizontal to near vertical for exact positioning without a thoracic positioner. These adjustments can be made from either end of the table.

A 76.2 mm (3 in) trough centered under the panels can be used to collect fluids. The table has a hook for a collecting pail which is offered as an accessory. Two tie-down attachments on each side of the table slide along the table edge and lock at any position.

Flat-Top

The extra large 152.5 x 56 cm (60 x 22 in) flat top is die-formed from one piece of heavy-gauge stainless steel with rounded corners, resulting in no welding, seams or sharp edges. The table center is slightly elevated so that fluids drain to a shallow trough around table edges. The drain outlet on the end has a hook for a collecting pail which is offered as an accessory.

Two sliding tie-down attachments on each side can be locked at any position along the edge of the table.

Hydraulic-Lift Base

The lift mechanism of the hydraulic-lift base is completely foot-operated, both up and down, allowing quick and easy adjustment of the table top to a comfortable height and position. Pumping action on a rubber pedal smoothly lifts the table top. Pressing down on a release bar causes the table top to glide down to the lowest position.

The v-top table height may be adjusted from 79 to 104 cm (31 to 41 in). The flat-top Table height may be adjusted from 75 to 100 cm (29-1/2 to 39-1/2 in).

The heavy base provides real stability and includes leveling screws. The base cover is made of heavy-gauge, satin finish, type 304, non-corrosive stainless steel to provide a lifetime of service.

Pedestal Base

This base provides a sturdy, stable support for the working surface, yet in no way interferes with your legs and feet as you move around the work surface. Four adjustable screws facilitate easy leveling.

The working height of the pedestal base with a v-top table is 94 cm (37 in); with a flat-top table, it is 89 cm (35 in).

The pedestal base is covered with heavy gauge, non-corrosive stainless steel.

One or Two End Tilting

These operating tables are offered with either one end or two end tilt mechanisms. Both types will revolve 360° and tilt lengthwise from horizontal to near vertical and lock at any angle.

With the single tilting tables only one end of the table can be raised. With the dual tilting

tables, either end can be raised. This dual tilting feature offers the convenience of not having to reposition the animal.

Heated Tops

The heated table tops aid in the prevention of heat loss during surgery and are available for both v-top and flat-top tables.

Heated coils located under the table provide even heat distribution. The temperature can be adjusted from 21° to 42° C (70° to 108°F) with the heating control box which easily mounts on a tie-down/restraint rod.

The total heating area measures 40.5 x 122 cm (16 x 48 in) on the v-top tables, 20 x 122 cm (8 x 48 in) for each panel, and measures 38 x 122 cm (15 x 48 in) on the flat-top tables.

| Large Animal Operating Table | | | | |
|------------------------------|---------------------|--------------|----------------|--------------|
| Table Style | Hydraulic-Lift Base | | Pedestal Base | |
| | Single Tilting | Dual Tilting | Single Tilting | Dual Tilting |
| V-Top | | | | |
| Heated 115 VAC, 60 Hz | CGS8234.66 | CGS8240.66 | CGS8246.66 | CGS8252.66 |
| Heated 230 VAC, 50 Hz | CGS8235.66 | CGS8241.66 | CGS8247.66 | CGS8253.66 |
| Non-Heated | CGS8236.66 | CGS8242.66 | CGS8248.66 | CGS8254.66 |
| Flat-Top | | | | |
| Heated 115 VAC, 60 Hz | CGS8237.66 | CGS8243.66 | CGS8249.66 | CGS8255.66 |
| Heated 230 VAC, 50 Hz | CGS8238.66 | CGS8244.66 | CGS8250.66 | CGS8256.66 |
| Non-Heated | CGS8239.66 | CGS8245.66 | CGS8251.66 | CGS8257.66 |

Catalog No.

CGS 8258.66

CGS 8259.66

Product

Collecting Pail, 11.9 liter (12-1/2 qt) capacity; seamless, noncorrosive stainless steel construction; 25.4 cm (10 in) deep with a 20 cm (7-7/8 in) diameter base

Base with Casters adds mobility to Hydraulic Lift and Pedestal Base Surgery Tables; two heavy-duty plated steel caster bars attach easily to existing leveling screws in the Table base; all four casters are equipped with locks