

HSE-Harvard* PLUGSYS System Cases and Minicase

Model 601 PLUGSYS Mainframe Case



PLUGSYS® Case Type 601

Specifications

Construction	Aluminium housing, brown plastic coated
Supply	110/220 V AC, 50/60 Hz, built-in line filter
Standard Accessories	Line cable, spare fuses, screw driver for fitting the function modules, document folder for the operating instructions of the function modules
Construction	Small housing with pivoting feet
Module Positions	7 slot units, max.
Power Consumption	30 W max.
Dimensions (H x W x D)	145 x 235 x 310 mm (5.7 x 9.3 x 12.2 in)
Weight	4 kg (8.8 lbs)

Catalog No.

CGS 8351.71

Product

Technical Data PLUGSYS Case Type 601

MiniCase with PLUGSYS Modules DBA and HRM



PLUGSYS® MiniCase Type 609

This MiniCase can be used as a stand-alone case and will accept PLUGSYS modules to a maximum of 4 slot units. Add-on options are available to meet individual requirements.

- | | |
|-----------------|--|
| Option 1 | Case width extension through internal straps, extra width 2 slot units; case can then take front panels up to 6 slot units |
| Option 2 | Power supply with additional +24 V (1.6 A) output increases max. consumption to 80 W |
| Option 3 | Carrying handle for secure transport in mobile use |
| Option 4 | 4 BNC sockets on back of unit for signal inputs or outputs |
| Option 5 | Empty MiniCase housing without power supply and mains input, to take non-electrical PLUGSYS modules, such as Pressure Regulator Module PRM Type 671/3; reduces housing width to 105 mm |
| Option 6 | Standard power supply to meet requirements for clinical applications to IEC 601/EN 60-601 and UL 544 |

Specifications

Dimensions, H x W x D	160 x 160 x 250 mm (Option 01 = 206 mm)
Weight	1.4 kg approx. without PLUGSYS modules
Accessories	Mains supply cable and operating instructions
Power Supply	85 to 264 V AC (40 Watts), output voltage +5 V DC (5 A) and ±12 V DC (0.5 A) for supplying PLUGSYS modules
Socket Combination	3-pin IEC mains with fuse and mains switch on back of housing
Housing	ABS plastics, flame-resistant to UL94VO, color RAL 7032 (stone gray), with ventilation slots at sides
Slot Width	4 max., possible to fit front panels of 6 slot units using internal straps, Option 1 case extension

Catalog No.

CGS 8352.71
CGS 8353.71
CGS 8354.71
CGS 8355.71
CGS 8356.71
CGS 8357.71
CGS 8358.71

Model

PLUGSYS Minicase Type 609
Option 1, Case Extension
Option 2, Additional Power Supply, +24 V (1.6 A)
Option 3, Carrying Handle
Option 4, 4 BNC Sockets on Rear
Option 5, Housing Without Power Supply
Option 6, Power Supply for Clinical Application