

## Sealpette Variable Volume Multi-Channel Pipettors



- Perfect tip sealing
- Excellent tip alignment
- Minimum pressure required to load tips
- Dispense head will rotate through 360° to give the user the most comfortable working angle
- Unique staggered tip-eject bar ensures easy tip ejection
- Compatible with a wide range of tips
- Easy maintenance and calibration with tool supplied
- Wide range of tips and accessories available
- 12 month warranty

The Sealpette Multi-Channel range features eight models covering the volume range 0.5 µl to 250 µl in 4, 8 and 12 channel versions. The 0.5 to 10 µl, 8 channel unit accepts ultra-microvolume tips.

The multi-channel Sealpettes have all the advantages of the single channel models, plus additional features designed to make pipetting into microplates easier, safer, and more accurate.

Sealpette Variable Volume Multi-Channel Pipettors					
Catalog No.	Channels	Range	Increment	Inaccuracy	Imprecision
CGS 8858.33	4	5 to 50 µl	5 µl	1.00%	0.50%
CGS 8859.33	4	50 to 250 µl	5.0 µl	0.70%	0.25%
CGS 8860.33	8	0.5 to 10 µl	0.1 µl	1.50%	1.50%
CGS 8861.33	8	5 to 50 µl	5 µl	1.00%	0.50%
CGS 8862.33	8	50 to 250 µl	5.0 µl	0.70%	0.25%
CGS 8863.33	12	0.5 to 10 µl	0.1 µl	1.50%	1.50%
CGS 8864.33	12	5 to 50 µl	5 µl	1.00%	0.50%
CGS 8865.33	12	50 to 250 µl	5.0 µl	0.70%	0.25%