

Outpatient® II



- 7000 footcandles (40% brighter)
- Color temperature of 3600°K; shadow-free design
- Blue filters and dichroic coatings keep beam cool
- Drift-free, self-balancing arm
- Low-voltage operation minimizes electrical hazards
- Optional wall dimmer switch
- Wide variety of mounting systems, including Fastrac and battery models
- Drop tube lengths for ceiling mounts is 76 cm (30 in)
- UL listed, CSA certified; mounting systems meet California Seismic codes
- 3-year warranty
- Enhanced illumination, plus focusability.
- Focuses with central removable, autoclavable SteriHandle™ II
- Friction knob allows user to position self-balancing arm without a tool
- Uses three 'optically improved' 50 watt halogen bulbs — each with 2000 hour life
- Floorstand model includes foot switch, locking casters and cord wrap

Why is the Outpatient® II judged to be the 'unanimous light of choice' for surgical suites, research centers, and nearly every application where optimal light and value pricing are required? The Outpatient® II offers the features most wanted, including focusability, pure white, intense light in a flood-type pattern and guaranteed, no-drift arm. With 3600 degrees K color temperature and three halogen bulbs wired in parallel to assure continuous light output, the Outpatient®

II is the one light all researchers, veterinarians, and physicians can use for minor surgeries, procedures and exams. The Outpatient® II's SteriHandle™ is autoclavable and accepts Disposable Light Covers. Plus, Outpatient® II single ceiling, double ceiling and combo models are standard with 0.76 (30 in) drop tubes. The Outpatient® II is available in complete models only due to its unique design.

Power				
Product	115 VAC, 60 Hz	220 VAC, 50 Hz	230 VAC, 50 Hz	240 VAC, 50 Hz
Outpatient® II Floorstand	CGS-8000.78	CGS-8006.78	CGS-8012.78	CGS-8018.78
Outpatient® II Single Ceiling	CGS-8001.78	CGS-8007.78	CGS-8013.78	CGS-8019.78
Outpatient® II Double Ceiling	CGS-8002.78	CGS-8008.78	CGS-8014.78	CGS-8020.78
Outpatient® II Wall Mount	CGS-8003.78	CGS-8009.78	CGS-8015.78	CGS-8021.78
Single Outpatient® II on Fastrac™	CGS-8004.78	CGS-8010.78	CGS-8016.78	CGS-8022.78
Double Outpatient® II on Fastrac™	CGS-8005.78	CGS-8011.78	CGS-8017.78	CGS-8023.78

Catalog No. Product

CGS 8024.78	High Intensity 50 Watt Replacement Bulbs, set of 3
CGS 8025.78	Outpatient® II SteriHandle
CGS 8026.78	Wall Dimmer Switch
CGS 8027.78	Sterile Disposable Light Covers, set of 25
CGS 8028.78	Extension Tube for Drop Ceiling Mount