



Basic Meter.

The simplicity you want with the precision you need.

Four keys do it all! Press the pH/mV key to toggle between pH and mV modes. Press the standardize key to auto-recognize a buffer or create a relative mV offset. Press Setup to clear buffers, check slope or select buffer set. Use Enter key to accept your changes.

Display is easy to read! Large display shows current pH or mV reading as well as the temperature and all buffers currently in use. A stability icon lets you know when your readings are stable.

Select a kit with the best electrode for your application. The standard Basic kit includes the meter, base, arm, power supply and "3-in-1" plastic-body pH/ATC combination electrode.

The Basic-Bio kit includes the meter, accessories and a "3-in-1" glass-body high performance combination electrode which is TRIS compatible. The Denver Basic-Bio kit is perfect for biotech applications.

- Accepts up to 3 calibration points
- Automatic buffer recognition of 22 buffers from 4 sets
- Automatic temperature compensation with active temperature reading
- Simultaneous display of measurement, temperature, stability icon and current buffers entered



Specifications/Ordering Information

pH	Range	-1.99 to +19.99
	Resolution	0.01
	Accuracy	±0.005
mV	Range	-1800.0 to +1800.0
	Resolution	0.1
	Accuracy	±0.3
Temp	Range	-5° to +105.0°C
	Accuracy	±0.4°C
	Compensation	Automatic, -5.0 to +105.0°C Manual at 20 or 25°C
Slope Control	Automatic, 90 to 105%	
Power Requirements	115V 50/60Hz (Other voltages available)	
Environmental Conditions	15 - 40°C @ 0 - 90% Relative Humidity	

Ordering Information

Denver BASIC kit includes: BASIC meter, power supply, electrode support arm and base, plastic-body Ag/AgCl combination pH/ATC electrode, instruction manual.

Denver BASIC-Bio kit includes: BASIC meter, power supply, electrode support arm and base, glass-body Tris-compatible combination pH/ATC electrode, instruction manual.

Meter only includes: BASIC meter, power supply, electrode arm and manual.

Basic Meter with Kit	Cat. No. 9209.X
Basic-Bio with Kit	Cat. No. 9240.X
Basic Meter Only	Cat. No. 9219.X

Available Voltages For All Meters	X = .1	115V 50/60Hz North America
	.2	220V 50/60Hz North America
	.3	230V 50/60Hz Europe
	.4	240V 50/60Hz United Kingdom
	.5	100V 50/60Hz Japan

When ordering, replace .X with the appropriate # for the desired voltage requirement.