

## Tubo a Gás Padrão

- Type 304 or 316 SS Acetone Washed
- Hi-EFF Grade SS Tubing Meets the Exact Specifications Required to Fabricate GC Columns
- Specially Tempered for Easy Bending
- Lengths to 50 ft.
- Type 304 is more ductile than Type 316
- Type 316 has higher corrosion resistance than Type 304



## Tipo 316

Part No.	Quantity
<b>CGS 1053.09</b> 1/8 in. OD x 0.085 in. (2.16 mm) ID: per ft (30.5 cm)	1
<b>CGS 1054.09</b> 3.18 mm OD x 2.16 mm ID: per meter	1
<b>CGS 1055.09</b> 1/8 in. OD x 0.085 in. (2.16 mm) ID: 50 ft. coil (15.26 m)	50
<b>CGS 1056.09</b> 1/4 in. OD x 0.210 in. (5.33 mm) ID: per ft (30.5 cm)	1
<b>CGS 1057.09</b> 6.35 mm OD x 5.33 mm ID: per meter	1
<b>CGS 1058.09</b> 1/4 in. OD x 0.210 in. (5.33 mm) ID: 50 ft. coil (15.26 m)	50

## Tipo 304

Part No.	Quantity
<b>CGS 1059.09</b> 1/8 in. OD x 0.085 in. (2.16 mm) ID: per ft (30.5 cm)	1
<b>CGS 1060.09</b> 3.18 mm OD x 2.16 mm ID: per meter	1
<b>CGS 1061.09</b> 1/8 in. OD x 0.085 in. (2.16 mm) ID: 50 ft. coil (15.26 m)	50
<b>CGS 1062.09</b> 1/4 in. OD x 0.210 in. (5.33 mm) ID: per ft (30.5 cm)	1
<b>CGS 1063.09</b> 6.35 mm OD x 5.33 mm ID: per meter	1
<b>CGS 1064.09</b> 1/4 in. OD x 0.210 in. (5.33 mm) ID: 50 ft. coil (15.26 m)	50

## Tubo Copper

- Economical choice for GC gas lines
- Pre-cleaned for GC use



Part No.	Quantity
<b>CGS 1065.09</b> 1/8 in. OD x 0.065 in. (1.65 mm) ID: 25 ft	25
<b>CGS 1066.09</b> 1/4 in. OD x 0.190 in. (4.83 mm) ID: 50 ft	50
<b>CGS 1067.09</b> 3/16 in. OD x 0.128 in. (3.25 mm) ID: 50 ft	50
<b>CGS 1068.09</b> 3/8 in. OD x 0.315 in. (8.01 mm) ID: 50 ft	50